

For the display cases data, please see page 14
Per i dati delle vetrine, vedere pag. 14

9
GN1/3

+2 +8
°C
TEMPERATURE RANGE

STATIC REFRIGERATION

200cm

DB20038



DB2610TN

1X7

390 lt

200cm

-2 +8
°C
TEMPERATURE RANGE

VENTILATED REFRIGERATION

ENERGY CLASS

CODE Codice	ENERGY CLASS Classe energetica	POWER Potenza	POWER SUPPLY Alimentazione	REFRIGERANT GAS Gas refrigerante	WORKING TEMPERATURE Temperatura d'esercizio	MAX TEMP. / HUMIDITY Temperatura / Umidità max.	CAPACITY Capacità
		W	volt		°C	°C / Hr	lt
DB2610TN	C	290	230/1N/50	R290	-2 +8	+30 / 55%	390
DB3600TN	C	290	230/1N/50	R290	-2 +8	+30 / 55%	456

**AS STANDARD / DI SERIE
DB2610TN**



DIGITAL CONTROLLER
Centralina elettronica



2 PLASTIC COATED SHELF 60X40CM
Griglia plastificata 60x40cm



2 STAINLESS STEEL PAIR OF GUIDES
Coppia guide INOX



LEVELING FEET
Piedini livellatori

**AS STANDARD / DI SERIE
DB3600TN**



DIGITAL CONTROLLER
Centralina elettronica



3 PLASTIC COATED SHELF 60X40CM
Griglia plastificata 60x40cm



3 STAINLESS STEEL PAIR OF GUIDES
Coppia guide INOX



LEVELING FEET
Piedini livellatori



DIGITAL CONTROLLER
Centralina elettronica



For the display cases data, please see page 14
Per i dati delle vetrine, vedere pag. 14



DB20038



DB3600TN



EXTERNAL DIMENSIONS Dimensioni esterne	INTERNAL DIMENSIONS Dimensioni Interne	NET WEIGHT Peso Netto	GROSS WEIGHT Peso Lordo	PACKING DIMENSIONS Dimensioni Imballo	IN COMBINATION WITH GLASS DISPLAY Abbinamenti con vetrina
cm (WxDxH)	cm (WxDxH)	kg	kg	cm	
202,5x80x100	105,2x63x58,9	327	347	206x83x120	DB2610TN + DB20038
202,5x80x102/106,5	156,2x63x58,9	306	326	206x83x120	DB3600TN + DB20038



DOOR RESISTANCE
Resistenza sulle porte



PLASTIFIED SHELF AND GUIDES IN STAINLESS STEEL
Griglia plastificata e guide in acciaio INOX



DRAWERS
Cassettiera